

EUROPEAN PATENT OFFICE

Patent Abstracts of Japan

PUBLICATION NUMBER : 11351306
PUBLICATION DATE : 24-12-99


APPLICATION DATE : 12-06-98
APPLICATION NUMBER : 10164797

APPLICANT : TOYOBO CO LTD;

INVENTOR : NONOMURA CHISATO;

INT.CL. : F16F 7/12 E01F 1/00 // B60R 19/03

TITLE : RESINOUS SHOCK ABSORBER AND
SHOCK ABSORBING METHOD USING
THE SAME



BEST AVAILABLE COPY

ABSTRACT : PROBLEM TO BE SOLVED: To provide a shock absorber having a superior shock absorbing ability, which has a small and lightweight structure, possesses a large energy absorbing capacity as compared with reaction force, and is capable of using both of on the ground and in the sea without maintenance.

SOLUTION: This is a shock absorber having a structure where hollow parts 2 surrounded by a partition wall 1 formed of material having a bending modulus of 5000 kgf/cm² or more are continuously and stratifiedly formed in the same direction, and having a honey-comb shape in cross section, wherein the hollow part partition wall 1 of the shock absorber is buckle-deformed, wherein a reaction-compressibility curve at the time of longitudinally compressing of the shock absorber satisfies the condition that yield strength is not less than 100 tf/m² and a compression energy absorbing capacity per unit volume is not less than 50 tf.m/m³, and wherein a reaction is made to be uniform with keeping an initial length when being added displacement in a longitudinal direction of the shock absorber until partially deformed, and being added displacement again after once removal.

COPYRIGHT: (C)1999,JPO